

View Online at <https://aerobasegroup.com/nsn/5930-01-143-5099>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

2.937 inches

**Overall Height:**

2.312 inches

**Overall Width:**

1.750 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.891 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 1: 30 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Pin at 1: 30 o'clock

**End Application:**

Test set

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

21 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

21 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0