## NSN 5930-01-143-6762

**Hazardous Locations/environmental Protection:** 

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-143-6762

Watertight
Overall Length:
3.150 inches
Body Diameter:
0.610 inches
Body Length:
1.410 inches
End Application:
2350-00-439-6242
Tempurature Sensing Element Type:
Immersion well
Width Across Flats:
Between 0.875 inches and 0.940 inches
Mounting Method:
Threaded bushing
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
14 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
0.500 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Connector, plug
Contact Load Current Rating:
3.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
225.00 actuation point degrees fahrenheit and 220.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
32.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical w/flange
Test Data Document:
81349-mil-s-12285 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5930-01-143-6762

Thermostatic Switch - Page 2 of 2



Tŀ	re	ad	Se	eries	De	sigr	ator
	_						

Nptf single threaded bushing

**Specification Data:** 

81349-mil-s-12285/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0