NSN 5930-01-143-6762

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-143-6762

Hazardous Locations/environmental Protection: Watertight **Overall Length:** 3.150 inches **Body Diameter:** 0.610 inches **Body Length:** 1.410 inches **End Application:** 2350-00-439-6242 **Tempurature Sensing Element Type:** Immersion well Width Across Flats: Between 0.875 inches and 0.940 inches **Mounting Method:** Threaded bushing **Features Provided:** Hermetically sealed case Thready Qty Per Inch (tpi): 14 single threaded bushing **Contact Action Stimulus:** Increase **Thread Size:** 0.500 inches single threaded bushing Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action **Terminal Type:** Connector, plug **Contact Load Current Rating:** 3.0 amperes resistive load second voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 225.00 actuation point degrees fahrenheit and 220.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 32.0 dc at sea level second voltage Media For Which Designed: Gas or liquid Style Designator: Cylindrical w/flange **Test Data Document:** 81349-mil-s-12285 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5930-01-143-6762

Thermostatic Switch - Page 2 of 2



Thread Series Designator:

Nptf single threaded bushing

Specification Data:

81349-mil-s-12285/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0