NSN 5930-01-143-6762

Hazardous Locations/environmental Protection:

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-143-6762

Watertight
Overall Length:
3.150 inches
Body Diameter:
0.610 inches
Body Length:
1.410 inches
End Application:
2350-00-439-6242
Tempurature Sensing Element Type:
Immersion well
Width Across Flats:
Between 0.875 inches and 0.940 inches
Mounting Method:
Threaded bushing
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
14 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
0.500 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Connector, plug
Contact Load Current Rating:
3.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
225.00 actuation point degrees fahrenheit and 220.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
32.0 dc at sea level second voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical w/flange
Test Data Document:
81349-mil-s-12285 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5930-01-143-6762

Thermostatic Switch - Page 2 of 2



Tŀ	re	ad	Se	eries	De	sigr	ator
	_						

Nptf single threaded bushing

Specification Data:

81349-mil-s-12285/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0