NSN 5930-01-144-2326

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-144-2326

view Offline at https://derobasegroup.com/hist//0000-01-144-2020
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
3.450 inches
Overall Height:
1.200 inches
Overall Width:
1.200 inches
Body Width:
0.975 inches
Body Height:
0.975 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.300 inches
Actuator Width:
0.740 inches
Actuator Color:
Red single actuator
Illuminated Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Con ind radio
Mounting Surface To Terminal End Distance:
3.150 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

NSN 5930-01-144-2326

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

17 socket, integrated wire termination

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0