

View Online at <https://aerobasegroup.com/nsn/5930-01-144-3232>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

0.500 inches

Overall Height:

1.305 inches

Overall Width:

0.450 inches

Bushing Length:

0.350 inches

Body Length:

0.500 inches

Body Width:

0.450 inches

Body Height:

0.410 inches

Actuator Style:

Rectangular

Actuator Height:

0.450 inches

Actuator Width:

0.100 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Color:

Silver single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Special Features:

On-on-on switch function; flatted actuator including antirotation option; chrome plated toggle, nickel plated brshings, standard terminations and unseal

Precious Material And Location:

Contact and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0