NSN 5930-01-144-5094

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-144-5094

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.180 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.211 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.430 inches

Individual Section Quantity:

···

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section periphery

Throw Quantity:

2 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

60.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

NSN 5930-01-144-5094

Rotary Switch - Page 2 of 2

A052b0



Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Detent Rotational Torque Range:
+0.500/+2.500 inch-pounds single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
350.0 milliamperes resistive load ac at sea level
Style Designator:
Tap, circular, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Specification Data:
81349-mil-s-3786/28 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: