NSN 5930-01-144-5465

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-144-5465 **Body Style:** Hole mounted **Overall Length:** 1.590 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.875 inches **Overall Height:** 0.822 inches **Overall Width:** 0.400 inches **Body Length:** 1.090 inches **Body Width:** 0.400 inches **Body Height:** 0.620 inches **Unthreaded Mounting Hole Diameter:** 0.114 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.406 inches **Actuator Length:** 0.110 inches **Actuator Style:** Rectangular **Actuator Height:** 0.062 inches **Actuator Width:** 0.165 inches **Actuator Free Position Height:** 0.578 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:**

0.3 grams

Switch Actuating Force:

7.5 grams

NSN 5930-01-144-5465

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	·Mc	WA	mar	١+.
н	CLU	alui	IVIC	vei	пег	H.

Between 0.056 pretravel inches and 0.040 overtravel inches and 0.013 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0