NSN 5930-01-144-5465

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-144-5465

Body Style:

Hole mounted

Overall Length:

1.590 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Height:

0.822 inches

Overall Width:

0.400 inches

Body Length:

1.090 inches

Body Width:

0.400 inches

Body Height:

0.620 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Height:

0.062 inches

Actuator Width:

0.165 inches

Actuator Free Position Height:

0.578 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.3 grams

Switch Actuating Force:

7.5 grams

NSN 5930-01-144-5465

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.056 pretravel inches and 0.040 overtravel inches and 0.013 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0