# NSN 5930-01-144-6617

Pressure Switch - Page 1 of 2

**Overall Height:** 



View Online at https://aerobasegroup.com/nsn/5930-01-144-6617

External deactuation point screw and external actuation point screw

2.812 inches
Overall Width:
5.188 inches
Body Length:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
End Application:
Cctv cvn70
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
2 pole, single throw, double make, both positions maintained
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+60.00/+350.00 actuation point pounds per square inch gage and +60.00/+350.00 deactuation point pounds per square inch gage
Contact Adjustment Type:

# NSN 5930-01-144-6617

Pressure Switch - Page 2 of 2



## **Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

### **Pressure Connector Type:**

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

## **Thread Series Designator:**

Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0