

View Online at <https://aerobasegroup.com/nsn/5930-01-145-1356>

Thread Class:

2a single mounting facility

Thread Length:

0.391 inches single mounting facility

Width Between Flats:

0.186 inches single actuator and 0.188 inches single actuator

Overall Length:

1.468 inches

First Flat Length:

0.281 inches single actuator

Shaft Length:

0.718 inches single actuator

Overall Diameter:

1.062 inches

Individual Section Quantity:

1

End Application:

5830-01-138-5073

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

Special Features:

0.138-32 unc-28 thd hole 0.234 in. Deep in shaft

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0