NSN 5930-01-145-2159

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-145-2159

Thread Class: 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.292 inches First Flat Length: 0.250 inches single actuator Flat Height: 0.094 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.625 inches single actuator **Overall Diameter:** 0.562 inches **Individual Section Quantity: End Application:** 6625-01-078-5571 **Switch Contact Basic Design:** Nonpile-up symmetrical Pole Quantity: 2 single section front **Throw Quantity:** 8 single section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 8 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Printed circuit **Contact Switching Action:**

Breaks before makes single section front

NSN 5930-01-145-2159

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 22.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 200.0 milliamperes resistive load dc at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Snap or line **Thread Series Designator:** Unf single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A052b0