# NSN 5930-01-145-2159

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-145-2159

# Thread Class:

2a single mounting facility

### Thread Length:

0.250 inches single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

1.292 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.094 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.625 inches single actuator

#### **Overall Diameter:**

0.562 inches

#### Individual Section Quantity:

1

# End Application:

6625-01-078-5571

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

2 single section front

#### **Throw Quantity:**

8 single section front

#### Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.250 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

8 single actuator

#### Shaft Type:

Round, flatted single actuator

# **Terminal Type:**

Printed circuit

#### **Contact Switching Action:**

Breaks before makes single section front

# NSN 5930-01-145-2159

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 22.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 200.0 milliamperes resistive load dc at sea level Precious Material And Location:

Contacts silver

**Precious Material:** 

Silver

Style Designator:

Snap or line

**Thread Series Designator:** 

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0