## NSN 5930-01-145-3210

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-145-3210
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
0.875 inches
Overall Height:
2.700 inches
Overall Width:
0.875 inches
Body Length:
0.750 inches
Body Width:
0.875 inches
Actuator Length:
0.700 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.700 inches
Actuator Inscription:
Preset single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
F/tf-15a acft
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes
inductive ac and 2.000 amperes lamp ac
Terminal Type And Quantity:
6 turret and 5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5930-01-145-3210

Push Switch - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A053a0