

View Online at <https://aerobasegroup.com/nsn/5930-01-145-4194>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Height:

8.000 inches

Overall Width:

3.300 inches

Unthreaded Mounting Hole Diameter:

0.266 inches

Distance Between Mounting Facility Centers:

4.250 inches

End Application:

An/wrr-3b

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

15.0 amperes resistive load first voltage and 15.0 amperes inductive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+30.00/+375.00 actuation point pounds per square inch and +10.00/+355.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

50.0 first voltage and 60.0 first voltage

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0