## NSN 5930-01-145-7343

Pressure Switch - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5930-01-145-7343

6.230 inches
Overall Height:
3.100 inches
Overall Width:
4.750 inches
Body Length:
3.600 inches
Unthreaded Mounting Hole Diameter:
0.265 inches
Longest Horizontal Distance Between Mounting Centers:
4.250 inches
Longest Vertical Distance Between Mounting Centers:
3.100 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -34.0 degrees celsius and 71.0 degrees celsius
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
7500.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
5.0 amperes resistive load second voltage and 3.0 amperes lamp load second voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+1950.00/+4200.00 actuation point pounds per square inch

## **Contact Adjustment Type:**

Internal actuation point serrated nut

## NSN 5930-01-145-7343

Pressure Switch - Page 2 of 2



## **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Pressure Connector Type:** 

Plain, threaded internal single connection

Media For Which Designed:

Gas

**Thread Series Designator:** 

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0