

| <b>NSN 5930-01-145-9232</b> Pressure Switch - Page 1 of 2     | ACTOBAS |
|---|---------|
| View Online at https://aerobasegroup.com/nsn/5930-01-145-9232 |         |
| Thread Class:   |         |
| 3b single pressure connection                                 |         |
| Inside Diameter:  |         |
| 0.540 inches single connection                                |         |
| Thread Length:  |         |
| 0.750 inches single pressure connection                       |         |

**Overall Length:** 

4.500 inches

**Overall Height:** 

**4.969** inches

**Overall Width:** 

2.750 inches

**Body Height:** 

3.875 inches

**Pressure Switch Type:** 

Differential

**Mounting Method:** 

Inlet connection

Thready Qty Per Inch (tpi):

18 single pressure connection

**Contact Action Stimulus:** 

Increase

**Proof Pressure:** 

225.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

**Terminal Type:** 

Screw

**Contact Load Current Rating:** 

5.0 amperes resistive load single voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point adjustable, preset

**Contact Adjustment Range:** 

+10.00/+150.00 actuation point pounds per square inch

**Contact Adjustment Type:** 

External actuation point knob

**Contact Stimulus Rating:** 

125.00 actuation point pounds per square inch and 10.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:** 

240.0 ac at sea level single voltage

## NSN 5930-01-145-9232

Pressure Switch - Page 2 of 2



## Pressure Connector Type: Plain, threaded internal single connection Frequency In Hertz: 60.0 single voltage Media For Which Designed: Gas Style Designator: Rectangular Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0