

View Online at <https://aerobasegroup.com/nsn/5930-01-146-1302>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

2.890 inches

Overall Height:

0.469 inches

Overall Width:

0.469 inches

Body Diameter:

0.469 inches

Bushing Length:

1.350 inches

Body Length:

0.850 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 0.660 inches and 0.690 inches

Actuator Roller Diameter:

Between 0.391 inches and 0.421 inches

Actuator Roller Width:

Between 0.059 inches and 0.064 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Airframe

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

112.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.250 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0