NSN 5930-01-146-4190

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-146-4190

Hazardous Locations/environmental Protection: Dustproof **Overall Length:** 1.375 inches **Overall Height:** 2.240 inches **Overall Width:** 2.190 inches **Mounting Slot Width:** 0.140 inches single mounting facility **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.075 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.562 inches single mounting facility **Operating Tempurature Range:** -40.0/+75.0 degrees celsius **Mounting Method:** Bracket single mounting facility and slot single mounting facility **Actuator Type:** Thumbwheel single actuator **Features Provided:** Illuminated **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 16 single actuator **Terminal Type:** Printed circuit **Contact Load Current Rating:** 125.0 milliamperes resistive load dc at sea level **Readout Indicator Marking:** 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 single section

Contact Arrangement Truth Table:

Bcd with complement, 1 pole - 16 positions single section

Color:

White single indicator marking

Precious Material And Location:

Contact surfaces gold

NSN 5930-01-146-4190

Code Indicating Wheel Switch - Page 2 of 2



Precious Material:
Gold
Style Designator:
Rectangular indicating
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0