

View Online at <https://aerobasegroup.com/nsn/5930-01-146-4190>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.375 inches

Overall Height:

2.240 inches

Overall Width:

2.190 inches

Mounting Slot Width:

0.140 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.075 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.562 inches single mounting facility

Operating Temperature Range:

-40.0/+75.0 degrees celsius

Mounting Method:

Bracket single mounting facility and slot single mounting facility

Actuator Type:

Thumbwheel single actuator

Features Provided:

Illuminated

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 single section

Contact Arrangement Truth Table:

Bcd with complement, 1 pole - 16 positions single section

Color:

White single indicator marking

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0