## NSN 5930-01-146-6614

Slide Switch - Page 1 of 2

Body Style:
Hole mounted
Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-146-6614

1.380 inches
Center To Center Distance Between Mounting Facilities Parallel To Length
1.125 inches
Overall Height:
1.000 inches
Overall Width:
0.734 inches
Body Length:
0.938 inches
Body Width:
0.734 inches
Body Height:
0.290 inches
Unthreaded Mounting Hole Diameter:
Between 0.136 inches and 0.140 inches
Actuator Length:
0.218 inches
Actuator Height:
0.344 inches
Actuator Width:
0.218 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained
Maximum Voltage Rating In Volts:
125.0 ac and 125.0 dc
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
3 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 4.000 amperes resistive ac
Special Features:
Terminal cover
Precious Material And Location:
Terminal surfaces and contact surfaces silver

N/a

**Terminal Type And Quantity:** 

9 tab, solder lug

Shelf Life:

## NSN 5930-01-146-6614

Slide Switch - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A053a0