

View Online at <https://aerobasegroup.com/nsn/5930-01-146-6624>

Body Style:

Hole mounted

Overall Length:

0.780 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

1.050 inches

Overall Width:

0.250 inches

Body Length:

0.780 inches

Body Width:

0.250 inches

Body Height:

0.370 inches

Unthreaded Mounting Hole Diameter:

0.089 inches

Actuator Length:

0.660 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

17.7 millimeters

Actuator Roller Diameter:

0.188 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

7.0 inch-ounces

Switch Actuating Force:

50.0 ounces

Actuator Movement:

0.375 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 30.000 milliamperes inductive dc and 200.000 milliamperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 500.000 milliamperes lamp ac

Precious Material And Location:

Terminal surfaces gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0