

View Online at <https://aerobasegroup.com/nsn/5930-01-146-6624>

**Body Style:**

Hole mounted

**Overall Length:**

0.780 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Height:**

1.050 inches

**Overall Width:**

0.250 inches

**Body Length:**

0.780 inches

**Body Width:**

0.250 inches

**Body Height:**

0.370 inches

**Unthreaded Mounting Hole Diameter:**

0.089 inches

**Actuator Length:**

0.660 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

17.7 millimeters

**Actuator Roller Diameter:**

0.188 inches

**Actuator Roller Width:**

0.125 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

7.0 inch-ounces

**Switch Actuating Force:**

50.0 ounces

**Actuator Movement:**

0.375 overtravel inches and 0.015 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 30.000 milliamperes inductive dc and 200.000 milliamperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 500.000 milliamperes lamp ac

**Precious Material And Location:**

Terminal surfaces gold

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A053a0