

View Online at <https://aerobasegroup.com/nsn/5930-01-146-6625>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dust resistant

**Overall Length:**

1.659 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.375 inches

**First Flat Length:**

0.500 inches single actuator

**Flat Height:**

0.198 inches single actuator and 0.201 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.625 inches single actuator

**Nonturn Device Radius:**

0.467 inches at 9: 00 o'clock and 0.475 inches at 9: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

480.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, slotted, flatted single actuator

**Terminal Type:**

Threaded stud

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Extra Long Reference Number:**

Ps-60101-w3/y9-70701-10/2c-31001-06

**Special Features:**

Fully enclosed

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unf single mounting facility

**Reference Number Differentiating Characteristics:**

As differentiated by extra long reference number

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0