NSN 5930-01-146-6640

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-146-6640

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
11.219 inches
Overall Height:
6.000 inches
Overall Width:
4.750 inches
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.375 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility and 0.410 inches single mounting facility
Individual Section Quantity:
12
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Longest Horizontal Distance Between Mounting Centers:
3.750 inches 2nd mounting facility
Longest Vertical Distance Between Mounting Centers:
5.250 inches 2nd mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
3 each section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:

onan Type.

Round single actuator

NSN 5930-01-146-6640Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Contact Switching Action:
Makes before breaks 6th section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
75.0 amperes resistive load lowest ac voltage rating at sea level
Special Features:
Round threaded hole shaft
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A052b0