## NSN 5930-01-146-6728

Lock Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-146-6728

| Thread Class:   |
|---|
| 2a  |
| Body Style:   |
| Bushing mounted   |
| Hazardous Locations/environmental Protection:                           |
| Dustproof   |
| Overall Length:   |
| 1.590 inches  |
| Overall Height:   |
| 0.875 inches  |
| Overall Width:  |
| 0.875 inches  |
| Body Diameter:  |
| 0.876 inches  |
| Bushing Length:   |
| 0.875 inches  |
| Body Length:  |
| 0.468 inches  |
| Maximum Voltage Rating In Volts:  |
| 115.0 ac and 30.0 dc  |
| End Application:  |
| 2f114wst  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Threaded bushing  |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Thread Size:  |
| 0.750 inches  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, both positions maintained single switch unit      |
| Contact Load Current Rating At Maximum Rated Voltage:                   |
| 250.000 milliamperes resistive dc and 250.000 milliamperes resistive ac |
| Precious Material And Location:   |
| Terminal surfaces gold and rotor contact surfaces rhodium               |
| Thread Series Designator:   |
| Uns   |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Shelf Life:   |
|   |

N/a

## NSN 5930-01-146-6728

Lock Switch - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A053a0