

View Online at <https://aerobasegroup.com/nsn/5930-01-146-7380>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.320 inches

Overall Height:

2.695 inches

Overall Width:

0.890 inches

Bushing Length:

0.470 inches

Body Length:

1.320 inches

Body Width:

0.890 inches

Body Height:

1.100 inches

Actuator Style:

Round

Actuator Diameter:

0.375 inches

Actuator Height:

0.875 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

230.0 ac and 30.0 dc

End Application:

Lathe eng flr

Mounting Surface To Terminal End Distance:

1.350 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

18.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes lamp dc and 6.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0