

View Online at <https://aerobasegroup.com/nsn/5930-01-147-0738>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.297 inches

Overall Height:

0.469 inches

Overall Width:

0.469 inches

Body Diameter:

0.469 inches

Bushing Length:

0.282 inches

Body Length:

0.749 inches

Case Material:

Metal

Actuator Diameter:

0.156 inches

Actuator Height:

0.136 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

5820-01-048-9110 radio set

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0