NSN 5930-01-147-0738

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Push Switch - Page 1 of 2

Thread Class:

Body Style:Bushing mounted

Overall Length: 1.297 inches Overall Height: 0.469 inches

2a



View Online at https://aerobasegroup.com/nsn/5930-01-147-0738

Overall Width:
0.469 inches
Body Diameter:
0.469 inches
Bushing Length:
0.282 inches
Body Length:
0.749 inches
Case Material:
Metal
Actuator Diameter:
0.156 inches
Actuator Height:
0.136 inches
Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
5820-01-048-9110 radio set
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

NSN 5930-01-147-0738

Push Switch - Page 2 of 2



Thread Series Designator:
Unef
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A053a0

Demilitarization: