

View Online at <https://aerobasegroup.com/nsn/5930-01-147-5199>

Overall Length:

2.750 inches

Outside Diameter:

0.500 inches single connection

Overall Diameter:

0.687 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Temperature Rating:

Between -53.0 degrees celsius and 71.0 degrees celsius

Mounting Method:

Inlet connection

Contact Action Stimulus:

Increase

Proof Pressure:

2100.00 pounds per square inch gage

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.0 amperes resistive load first voltage and 4.0 amperes inductive load first voltage 7.0 amperes resistive load second voltage and 4.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

500.00 actuation point pounds per square inch gage and 250.00 deactuation point pounds per square inch gage and 350.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

20.0 dc at sea level first voltage 45.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0