## NSN 5930-01-147-5229

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-147-5229

**Thread Class:** 2a single mounting facility Thread Length: 0.312 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.666 inches **Overall Height:** 0.868 inches **Overall Width:** 0.875 inches First Flat Length: 0.250 inches single actuator Flat Height: 0.219 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.375 inches single actuator **Individual Section Quantity:** 2 **Nonturn Device Type:** Slotted bushing at 3: 00 o'clock **Operating Tempurature Range:** -65.0/+125.0 degrees celsius **End Application:** Receiving set an/wlq- (v) **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section front **Throw Quantity:** 5 each section rear **Mounting Method:** Threaded bushing single mounting facility and printed circuit single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level

00.0 00 01 000 10 001

Shaft Flat/slot Angular Location:

105.0 degrees from nonturn device single actuator

## **NSN 5930-01-147-5229**Rotary Switch - Page 2 of 2



Rotor Through Connection Quantity:
2 each section
Switch Actuator Indexing Position Quantity:
5 single actuator
Shaft Type:
Round, hollowed, flatted single actuator
Terminal Type:
Printed circuit
Contact Switching Action:
Makes before breaks each section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Detent Rotational Torque Range:
+4.000/+32.000 inch-ounces single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
500.0 milliamperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level
Special Features:
Concentric shaft provision
Precious Material And Location:
Contacts and terminal surfaces gold and contacts silver
Precious Material:
Gold and silver
Style Designator:
Wafer, printed board, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A052b0