NSN 5930-01-147-6880

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-147-6880

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Corrosion resistant and fungus resistant
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.812 inches
Body Length:
3.500 inches
Body Width:
1.156 inches
Body Height:
1.469 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.125 inches
Actuator Style:
Round
Actuator Height:
1.594 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained and center position maintained
Actuator Position-locking Relationship:
Up position no locking action and down position locked in and out and center position locked in and out
Maximum Voltage Rating In Volts:
120.0 ac
End Application:
Transmitting set, radio an/frt-64
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Pile-up Contact Form Arrangement:
1a1b1c 2nd position
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
14 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-01-147-6880

Lever Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0