

View Online at <https://aerobasegroup.com/nsn/5930-01-147-6905>

Thread Class:

2b single mounting facility

Overall Length:

5.812 inches

Overall Height:

3.312 inches

Overall Width:

2.875 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.500 inches single actuator

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.875 inches single mounting facility

End Application:

An/frit-64 transmitting set

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

11 each section rear

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

20.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, panel mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0