## NSN 5930-01-147-6906

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-147-6906

View Online at https://aerobasegroup.com/nsn/5930-01-147-6906
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Shaft Length:
3.000 inches single actuator
Individual Section Quantity:
1
Knob Manufacturer Code:
52151
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Facility Circle Radius:
1.000 inches single mounting facility
Mounting Method:
Threaded hole single mounting facility
Features Provided:
Actuator knob
Thread Size:
0.250 inches single mounting facility
Contact Voltage Rating In Volts:
600.0 highest dc voltage rating at sea level
Mounting Facility Pattern:
Three position circular single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Threaded stud
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
8.0 amperes resistive load lowest dc voltage rating at sea level and 4.0 amperes inductive load lowest dc voltage rating at sea level
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:

Tap, circuit selector

## NSN 5930-01-147-6906

Rotary Switch - Page 2 of 2



Ī	hread	<b>Series</b>	Desig	nator:

Unf single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0