NSN 5930-01-147-6906

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-147-6906

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Shaft Length:

3.000 inches single actuator

Individual Section Quantity:

1

Knob Manufacturer Code:

52151

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.000 inches single mounting facility

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 highest dc voltage rating at sea level

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Threaded stud

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

8.0 amperes resistive load lowest dc voltage rating at sea level and 4.0 amperes inductive load lowest dc voltage rating at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

NSN 5930-01-147-6906

Rotary Switch - Page 2 of 2

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0

