

View Online at <https://aerobasegroup.com/nsn/5930-01-148-1883>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

Between 1.184 inches and 1.216 inches

Overall Height:

3.250 inches

Overall Width:

Between 0.944 inches and 0.976 inches

Body Length:

Between 1.075 inches and 1.205 inches

Body Width:

Between 0.859 inches and 0.891 inches

Body Height:

3.110 inches

Actuator Length:

Between 1.024 inches and 1.056 inches

Actuator Style:

Rectangular

Actuator Height:

0.140 inches

Actuator Width:

Between 0.784 inches and 0.816 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Red single actuator and red single actuator

Illuminated Actuator Color Sequence:

Top half of actuator red bottom half of actuator red

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Special Features:

Horizontally split screen and two diffusers

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0