## NSN 5930-01-148-3132

Thermostatic Switch - Page 1 of 2

Unc single threaded stud



View Online at https://aerobasegroup.com/nsn/5930-01-148-3132

Thread Class:
2a single threaded stud
Hazardous Locations/environmental Protection:
Humidity resistant and vibration resistant
Overall Height:
0.831 inches
Body Height:
0.315 inches
Overall Diameter:
0.640 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Threaded stud
Thready Qty Per Inch (tpi):
32 single threaded stud
Contact Action Stimulus:
Increase
Thread Size:
0.138 inches single threaded stud
Nonpile-up Contact Arrangement:
A male primate theory are more than the primate and are made and are the primate and a
1 pole, single throw, normally closed, momentary action
Terminal Type:
Terminal Type:
Terminal Type: Tab, solder lug
Terminal Type: Tab, solder lug Contact Load Current Rating:
Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage
Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability:
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating:
Terminal Type: Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating: 266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts:
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating: 266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts: 30.0 ac at sea level third voltage
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating: 266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts: 30.0 ac at sea level third voltage  Media For Which Designed:
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating: 266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts: 30.0 ac at sea level third voltage  Media For Which Designed: Gas or liquid
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating: 266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts: 30.0 ac at sea level third voltage  Media For Which Designed: Gas or liquid  Precious Material And Location:
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating: 266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts: 30.0 ac at sea level third voltage  Media For Which Designed: Gas or liquid  Precious Material And Location: Contacts silver
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating: 266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts: 30.0 ac at sea level third voltage  Media For Which Designed: Gas or liquid  Precious Material And Location: Contacts silver  Precious Material:
Terminal Type: Tab, solder lug  Contact Load Current Rating: 5.0 amperes resistive load third voltage  Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable  Contact Stimulus Rating: 266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit  Contact Voltage Rating In Volts: 30.0 ac at sea level third voltage  Media For Which Designed: Gas or liquid  Precious Material And Location:  Contacts silver  Precious Material: Silver

## NSN 5930-01-148-3132

Thermostatic Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0