NSN 5930-01-148-3132

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-148-3132

Thread Class:

2a single threaded stud

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Overall Height:

0.831 inches

Body Height:

0.315 inches

Overall Diameter:

0.640 inches

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32 single threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches single threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

266.00 actuation point degrees fahrenheit and 236.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 ac at sea level third voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Disc

Thread Series Designator:

Unc single threaded stud

NSN 5930-01-148-3132

Thermostatic Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0

