NSN 5930-01-148-3300

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-148-3300

Thread Class:
2a all threaded stud
Thread Length:
0.313 inches all threaded stud
Overall Height:
0.786 inches
Body Height:
0.290 inches
Overall Diameter:
0.605 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit
Mounting Method:
Threaded stud
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
32 all threaded stud
Contact Action Stimulus:
Increase
Thread Size:
0.164 inches all threaded stud
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
Contact Load Current Rating: 4.0 amperes resistive load single voltage
-
4.0 amperes resistive load single voltage
4.0 amperes resistive load single voltage Contact Adjustability:
4.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
4.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
4.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 167.00 actuation point degrees fahrenheit and 140.00 deactuation point degrees fahrenheit
4.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 167.00 actuation point degrees fahrenheit and 140.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
4.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 167.00 actuation point degrees fahrenheit and 140.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level single voltage
4.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 167.00 actuation point degrees fahrenheit and 140.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level single voltage Media For Which Designed:
4.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 167.00 actuation point degrees fahrenheit and 140.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level single voltage Media For Which Designed: Gas or liquid
4.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 167.00 actuation point degrees fahrenheit and 140.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level single voltage Media For Which Designed: Gas or liquid Style Designator:

NSN 5930-01-148-3300

Thermostatic Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0