NSN 5930-01-148-3886

Thermostatic Switch - Page 1 of 2

Cylindrical



View Online at https://aerobasegroup.com/nsn/5930-01-148-3886

| Overall Height: |
|---|
| 2.125 inches |
| Body Diameter: |
| 5.750 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.219 inches |
| Distance Between Mounting Facility Centers: |
| 2.000 inches |
| Capillary Tube Length: |
| 120.0 inches |
| Bulb Length: |
| 3.000 inches |
| Bulb Diameter: |
| 0.688 inches |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Mounting Method: |
| Bracket and unthreaded hole |
| Features Provided: |
| Hermetically sealed case and electrical access port |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 5.0 amperes resistive load second voltage |
| Contact Adjustability: |
| Actuation point adjustable and deactuation point adjustable |
| Contact Adjustment Range: |
| +100.00/+200.00 actuation point degrees fahrenheit and +100.00/+200.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External actuation point knob and external deactuation point knob |
| Contact Voltage Rating In Volts: |
| 230.0 ac at sea level second voltage |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |

NSN 5930-01-148-3886

Thermostatic Switch - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0