

View Online at <https://aerobasegroup.com/nsn/5930-01-148-6837>

Body Style:

Hole mounted

Overall Length:

1.935 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Height:

1.239 inches

Overall Width:

0.400 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

1.020 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.810 inches

Actuator Roller Diameter:

0.190 inches

Actuator Roller Width:

0.190 inches

Maximum Voltage Rating In Volts:

125.0 ac

End Application:

Los angeles class ss (688), wasp class lhd, sturgeon class ssn(637), ticonderoga class cg(47), spruance class dd(963) , tarawa class lha, oliver perry class ffg, forrestal class cv, blue ridge class lcc-19, nimitz class cvn

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 grams

Criticality Code Justification:

Feat

Switch Actuating Force:

35.0 grams

Actuator Movement:

Between 0.125 pretravel inches and 0.085 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0