NSN 5930-01-148-8399

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-148-8399

Overall Length:
5.188 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Bulb
Mounting Method:
Bracket and unthreaded hole and threaded bushing
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
14 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
0.500 inches single threaded bushing
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+140.00/+215.00 actuation point degrees fahrenheit and +140.00/+215.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage

NSN 5930-01-148-8399

Thermostatic Switch - Page 2 of 2



М	ciba	For	Which	Desig	ınad.
ΙVΙ	eula	TO1	VVIIICI	ı Desid	mea.

Gas or liquid

Thread Series Designator:

Npt single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0