# NSN 5930-01-149-2971

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-149-2971

## Body Style:

Panel mount

## Hazardous Locations/environmental Protection:

Salt spray resistant and shock resistant and vibration resistant

#### **Overall Length:**

1.120 inches

#### **Overall Height:**

2.720 inches

#### **Overall Width:**

0.870 inches

#### **Body Length:**

1.060 inches

Body Width:

#### 0.810 inches

Body Height:

# 2.440 inches

Actuator Length:

#### 0.934 inches

Actuator Style:

Rectangular

#### Actuator Height:

0.070 inches

## Actuator Width:

0.684 inches

#### Actuator Color:

White single actuator

#### Illuminated Actuator Color:

White single actuator

#### Actuator Inscription:

Battery/ bank 2/ on bus single actuator

# Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### End Application:

Central office, telephone, automatic an/ttc-39

## Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

# Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000

amperes inductive ac and 750.000 milliamperes lamp ac

# NSN 5930-01-149-2971

Push Switch - Page 2 of 2

# Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

