# NSN 5930-01-149-6801

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-149-6801

## **Overall Height:**

0.638 inches

## **Body Height:**

Between 0.280 inches and 0.395 inches

### **Overall Diameter:**

Between 0.540 inches and 0.640 inches

### Tempurature Sensing Element Type:

Internal sensor

#### **Operating Tempurature Rating:**

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

#### **Mounting Method:**

Clamp

**Features Provided:** 

#### Hermetically sealed case

**Contact Action Stimulus:** 

Increase

#### Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

#### **Terminal Type:**

Tab, solder lug

## **Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

#### Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

#### **Contact Stimulus Rating:**

60.00 actuation point degrees fahrenheit and 40.00 deactuation point degrees fahrenheit

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

#### **Frequency In Hertz:**

60.0 first voltage

#### Media For Which Designed:

Gas or liquid

#### Style Designator:

Disc

#### Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-s-24236/1 government specification

## Shelf Life:

N/a

### Unit Of Measure:

# NSN 5930-01-149-6801

Thermostatic Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A048b0

