## NSN 5930-01-149-7099

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-149-7099

Body Style:
Hole mounted
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
0.915 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.880 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Height:
0.055 inches
Actuator Free Position Height:
0.625 inches
Maximum Voltage Rating In Volts:
250.0 dc
End Application:
Main diesel engine model mtf2-4rn-rh used onboard 378 ft whec coast guard vessels
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:

5.0 ounces

**Switch Actuating Force:** 

Between 12.0 ounces and 18.0 ounces

## NSN 5930-01-149-7099

Sensitive Switch - Page 2 of 2



Δ	cti	Jato	r N	lov	em	en	ŧ.
м	CLI	uaic	JI IV	w	em		ш.

0.040 pretravel inches and 0.005 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

3.000 amperes resistive dc

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0