## NSN 5930-01-150-0232

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-150-0232

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
5.438 inches
Overall Height:
2.906 inches
Overall Width:
2.812 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
D
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section rear
Throw Quantity:
3 single section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
600.0 ac at sea level
Switch Actuator Momentary Position:
Counterclockwise single actuator
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Terminal Type:
Tab w/saraw

Tab w/screw

## NSN 5930-01-150-0232

Rotary Switch - Page 2 of 2



C	nn	ta	٠ŧ	Sw	ritc	hir	'n	Δς	tior	١.
U	ווט	ιa	Ŀι	JW	IILL	1111	ıu	Mu	เเบเ	ı,

Makes before breaks single section rear

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

**Contact Load Current Rating:** 

20.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A052b0