NSN 5930-01-150-0281

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-150-0281

View Online at https://aerobasegroup.com/nsn/5930-01-150-0281
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof and moisture resistant
Overall Length:
6.375 inches
Overall Height:
2.500 inches
Overall Width:
2.250 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.031 inches
Actuator Roller Diameter:
0.500 inches
Housing Length:
6.375 inches
Housing Width:
2.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.125 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.500 inches
Maximum Voltage Rating In Volts:
550.0 ac and 550.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
72.0 ounces

Actuator Movement:

0.125 pretravel inches and 0.218 overtravel inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 1.200 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

8 screw

NSN 5930-01-150-0281

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0