## NSN 5930-01-150-0281

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-150-0281

| View Online at https://aerobasegroup.com/nsn/5930-01-150-0281                      |
|--|
| Body Style:  |
| Hole mounted   |
| Hazardous Locations/environmental Protection:                                      |
| Dustproof and moisture resistant   |
| Overall Length:  |
| 6.375 inches   |
| Overall Height:  |
| 2.500 inches   |
| Overall Width:   |
| 2.250 inches   |
| Actuator Style:  |
| Roller plunger   |
| Actuator Free Position Height:   |
| 1.031 inches   |
| Actuator Roller Diameter:  |
| 0.500 inches   |
| Housing Length:  |
| 6.375 inches   |
| Housing Width:   |
| 2.250 inches   |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length:  |
| 4.125 inches   |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width:   |
| 1.500 inches   |
| Maximum Voltage Rating In Volts:   |
| 550.0 ac and 550.0 dc  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Unthreaded hole  |
| Nonpile-up Contact Arrangement:  |
| 2 two circuit, double break/double make, one position momentary single switch unit |
| Switch Actuating Force:  |
| 72.0 ounces  |

**Actuator Movement:** 

0.125 pretravel inches and 0.218 overtravel inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

100.000 milliamperes resistive dc and 1.200 amperes resistive ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

8 screw

## NSN 5930-01-150-0281

Sensitive Switch - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0