

View Online at <https://aerobasegroup.com/nsn/5930-01-150-1647>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Salt spray resistant

Case Material:

Metal

Actuator Length:

1.562 inches

Actuator Style:

Roller arm

Actuator Height:

1.562 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.310 inches

Housing Height:

2.562 inches

Housing Length:

3.688 inches

Housing Width:

2.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.812 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.938 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Switch Actuating Force:

Between 8.0 inch-ounces and 20.0 inch-ounces

Actuator Movement:

0.219 pretravel inches and 90.0 overtravel degrees and 0.007 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0