NSN 5930-01-150-1647

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-150-1647

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Salt spray resistant
Case Material:
Metal
Actuator Length:
1.562 inches
Actuator Style:
Roller arm
Actuator Height:
1.562 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.310 inches
Housing Height:
2.562 inches
Housing Length:
3.688 inches
Housing Width:
2.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.812 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.938 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, two positions momentary single switch unit
Switch Actuating Force:

Between 8.0 inch-ounces and 20.0 inch-ounces

Actuator Movement:

0.219 pretravel inches and 90.0 overtravel degrees and 0.007 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

NSN 5930-01-150-1647

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0